



MtM+ Technology

M908

LoRa Communication + MCU Module

With Intel Quark

Preliminary DATASHEET
10th April, 2018

Table of Contents

1	Product Brief.....	1
1.1	Brief.....	1
1.2	Part Number.....	1
2	Features and Applications	2
3	Block Diagram	2
4	Technical Specifications.....	3
4.1	Absolute Maximum Ratings	3
4.2	Operation Condition	3
4.3	Wireless Specifications	3
4.4	LoRa RF Performance	4
4.4.1	Band 915 MHz (US)	4
4.4.2	Band 868 MHz (EU)	5
4.4.3	Band 780 MHz (CN)	6
4.4.4	Band 923 MHz (AS).....	7
4.4.5	Band 922 MHz (KR).....	8
4.4.6	Band 433 MHz (EU)	9
4.4.7	Band 490 MHz (CN)	10
4.5	Power Consumption	11
5	Dimensions	12
6	Pin Assignments.....	13
7	Recommended Footprint.....	14
8	Reference Design Circuit.....	15
9	Recommended Reflow Profile	16
10	SiP Module Preparation.....	17
10.1	Handling	17
10.2	SMT Preparation	17
11	Package Information.....	18
12	Document History.....	19

1 Product Brief

1.1 Brief

The SiP module includes Intel Quark SE C1000 and Semtech SX1276.

Low-power-consumption system-on-chip that provides edge analytics by combining an x86 MCU with a sensor subsystem and pattern-matching capability through a hardware-accelerated engine.

The Semtech SX1276 carries LoRa® long range modem that provides ultra-long range spread spectrum communication and high interference immunity whilst minimising current consumption.

For the software and driver development, we provide extensive technical document and reference software code for the system integration. Hardware evaluation kit and development utilities are ready to applied.

KEY FEATURES

- Intel® Quark™ SE C1000 32 MHz Microcontroller
- Semtech SX1276 LoRa Transceiver
- 384 kB NVM, 8 kB OTP NVM, 80 kB SRAM
- LGA-144 package, 12 x 12 x 1.3 mm
- 24 GPIO
- SPI / UART / PWM / I²C interfaces
- -40°C to 85°C operating temperature

1.2 Part Number

Part Number	RF Band	Description
M908H	868, 915, 780, 922, 923MHz	EU868, US915 ISM Band
M908L	433, 490MHz	EU433, AS430 ISM Band

2 Features and Applications

Feature List


- MCU
 - Intel 32MHz Quark MCU (C1000)
 - 32MHz DSP for sensor subsystem
 - 8 kB 2-way L1 instruction cache
 - Low Latency Data Tightly Coupled Memory (TCM)
 - Interface to on-die SRAM: 1.49 DMIPs/MHz
- LoRa transceiver
 - Full Band 868/915/922/923/780/433/490 MHz
 - Supports end-device class A/B/C
 - 168 dB maximum link budget
 - +20 dBm – 100 mW constant RF output vs. V supply
 - +14 dBm high efficiency PA
 - High sensitivity: Down to -148 dBm
 - Programmable bit rate up to 300 kbps
- Memory
 - 384 kB of on-die NVM + 8 kB OTP on-die NVM
 - 80 kB of on-die SRAM
- Power management
 - SiP Status: Active, Sleep and off
 - Sensor subsystem: Sensing active, sensing wait and sensing standby
 - Platform power DC-DC 1.8V, 3.3V
- Industry standard I/O hardware
 - USB 1.1 FS device
 - 2 I²C / 2 SPI / 2 UART, 4 Timers, 4 PWM
- Sensor subsystem interface
 - 2 I²C / 2 SPI
 - 4 channel 12-bit ADC
 - 2 timers
- Industry standard I/O hardware characteristics
 - Operation range: -40°C ~ +85°C
 - LGA-144 pins, 12 x 12 x 1.3 mm

Applications

- Utility metering and lighting control
- Long range irrigation systems
- Wireless alarm and security systems
- Internet of Things (IoT)
 - Industrial monitoring and control
 - Sensor networks
 - Home and building automation

3 Block Diagram

There is fully integration module with Semtech SX1276, 32MHz low power crystal. Intel C1000 Quark Processor.



4 Technical Specifications

Operation and storage condition

4.1 Absolute Maximum Ratings

Item	Description		Value	Unit
Ratings Over Operating Free-Air Temperature Range				
1	Supply voltage	All supply pins must have the same voltage	3.3	V
2	Voltage on any pin		3.3/1.8	V
3	Storage temperature range		-40 ~ 110	°C

4.2 Operation Condition

Operating Condition	Min	Typical	Max	Unit
VCC	--	3.3	--	V
Operation ambient temperature range	-40	--	85	°C

4.3 Wireless Specifications


The M908 module is compliant with the following features and standards:

Features	Description
Frequency	868/915/922/923/780/433/490 MHz
Modulation Method	FSK, GFSK and LoRa Technology Modulation
Sensitivity	Down to -148 dBm


4.4 LoRa RF Performance

4.4.1 Band 915 MHz (US)

Transmitter output power: (Tx power setting from 14 ~ 20 dBm)




Receiver sensitivity and SNR: (w/ Spreading Factor and Bandwidth)




4.4.2 Band 868 MHz (EU)

Transmitter output power: (Tx power setting from 14 ~ 20 dBm)




Receiver sensitivity and SNR: (w/ Spreading Factor and Bandwidth)




4.4.3 Band 780 MHz (CN)

Transmitter output power: (Tx power setting from 14 ~ 20 dBm)




Receiver sensitivity and SNR: (w/ Spreading Factor and Bandwidth)




4.4.4 Band 923 MHz (AS)

Transmitter output power: (Tx power setting from 14 ~ 20 dBm)




Receiver sensitivity and SNR: (w/ Spreading Factor and Bandwidth)




4.4.5 Band 922 MHz (KR)

Transmitter output power: (Tx power setting from 14 ~ 20 dBm)




Receiver sensitivity and SNR: (w/ Spreading Factor and Bandwidth)




4.4.6 Band 433 MHz (EU)

Transmitter output power: (Tx power setting from 14 ~ 20 dBm)




Receiver sensitivity and SNR: (w/ Spreading Factor and Bandwidth)




4.4.7 Band 490 MHz (CN)

Transmitter output power: (Tx power setting from 14 ~ 20 dBm)



Receiver sensitivity and SNR: (w/ Spreading Factor and Bandwidth)




4.5 Power Consumption

Item	Typ.	Units
TX with 18.7dBm at 915MHz (Continue Tx with RF Test FW)	149	mA
TX with 18.3dBm at 433MHz (Continue Tx with RF Test FW)	136	mA
Standby Mode with RF Test FW	32 ~ 33	mA
Rx (Continue Rx with RF Test FW)	~40	mA
Deep Sleep	~2	mA

5 Dimensions

The size and thickness of the M908 module are 12mm (W) x 12mm (L) x 1.3mm (H):



Dimension Detail


	Symbol	Common Dimensions		
		MIN.	NOM.	MAX.
Package :	PIM	---	---	---
Body Size:	X	E	12.000	
	Y	D	12.000	
Ball Pitch :	e	1.000		
Total Thickness :	A	---	1.332	1.402
Mold Thickness :	M	---	1.000	1.030
Substrate Thickness :	S	---	0.332	0.372
Solder Thickness :	T	---	---	---
Lead Width	W	0.480	0.500	0.520
BODY CENTER TO CONTACT BALL	SD	0.500		
	SE	0.500		
Package Edge Tolerance :	aaa	0.100		
Lead Count :	n	144		
EDGE BALL CENTER TO CENTER:	D1	11.000		
	E1	11.000		

6 Pin Assignments


	1	2	3	4	5	6	7	8	9	10	11	12
A	RF_IO	GND	GND	GND	GND	VCC_AON_1P8	TR_RXT	GPIO[21]	GPIO[24]	GPIO[25]	AREF_PA_D	GND
B	GND	GND	GND	GND	GND	GND	SPI1_SS_MISO	GPIO[22]	GPIO[23]	GPIO[26]	GND	VCC_IO_A_ON
C	I2C0_SDA	I2C0_SCL	I2C1_SCL	I2C1_SDA	SPI0_SS_MISO	SPI0_SS_CS_B[3]	SPI1_SS_MOSI	SPI1_SS_CS_B[2]	GND	GPIO[27]	PWM[3]	PWM[2]
D	I2C1_SS_S_CL	I2C1_SS_S_DA		GND	GND	SPI0_SS_SCK	SPI0_SS_CS_B[2]	SPI1_SS_SCK	SPI1_SS_CS_B[3]	GND	GND	PWM[0] PWM[1]
E	I2C0_SS_S_CL	I2C0_SS_S_DA		GND	GND	SPI0_SS_MOSI	SPI0_SS_CS_B[1]	SPI1_SS_CS_B[1]	SPI1_SS_CS_B[0]	GND	RST_B	GND VCC_HOST_1P8_PG
F	ADC[0]	GPIO_SS_[5]	GPIO_SS_[3]		GND	GND	SPI0_SS_CS_B[0]	TDI	TDO	GND	GND	VCC_AVD_OPM_2P6 VCC_AVD_OPM_2P6
G	USB_NP	USB_DP		GND	GND	GND	TRST_B	TMS	GND	PLT_REG_EN	GND	VCC_PLT_1P8_IND
H	GND	GPIO_SS_[4]	GPIO_SS_[2]		GND	GPIO[1]	TCK	AON_GPIO[0]	AON_GPIO[4]	AON_GPIO[2]	GND	VCC_PLT_1P8
J	UART0_TX_D	UART0_RX_D		GND	GND	GPIO[2]	GPIO[3]	AON_GPIO[5]	AON_GPIO[3]	AON_GPIO[1]	GND	VCC_PLT_3P3
K	GND	GND		GND	GND	GND	GND	GND	GND	GND	GND	VCC_PLT_3P3_IND
L	OSC32M_OUT		GND	UART1_TX_D	UART1_CTS	VCC_CMP	GND	GND	GND	VBAT_SOC	GND	VCCOUT_AON_1P8 VCC_HOST_1P8_IND
M	OSC32M_IN		GND	UART1_RX_D	UART1 RTS	VCC_USB_3P3	VCC_ADC	VDD_RFS	TR_NRESET	VBAT_SOC	GND	VCC_HOST_1P8 VCC_HOST_1P8
	RF	Clock	UART	PWM	ADC	GND						
	Power	USB	SPI	JTAG	AON_GPIO	Others						

7 Recommended Footprint


Suggest on PCB: SMD (1:1)



8 Reference Design Circuit



9 Recommended Reflow Profile



Profile Condition

- Suitable for Lead-Free solder
- Between 155 ~ 160°C: 60~90 sec.
- Above 220°C: 60 ~ 90 sec.
- Peak Temperature: 240 ~ 245°C (<10 sec.)

10 SiP Module Preparation



10.1 Handling

Handling the module must wear the anti-static wrist strap to avoid ESD damage. After each module is aligned and tested, it should be transport and storage with anti-static tray and packing. This protective package must be remained in suitable environment until the module is assembled and soldered onto the main board.

10.2 SMT Preparation


1. Calculated shelf life in sealed bag: 6 months at <40°C and <90% relative humidity (RH).
2. Peak package body temperature: 250°C.
3. After bag was opened, devices that will be subjected to reflow solder or other high temperature process must.
 - a. Mounted within: 72 hours of factory conditions <30°C /60% RH.
 - b. Stored at \leq 10% RH with N2 flow box.
4. Devices require baking, before mounting, if:
 - a. Package bag does not keep in vacuumed while first time open.
 - b. Humidity Indicator Card is >10% when read at $23\pm 5^\circ\text{C}$.
 - c. Expose at 3A condition over 8 hours or Expose at 3B condition over 24 hours.
5. If baking is required, devices may be baked for 12 hours at $125\pm 5^\circ\text{C}$.

11 Package Information



12 Document History

Date	Modifications	Version
Mar. 08, 2017	Preliminary version	1.0
Jan. 03, 2018	Add the power consumption	1.1
Feb. 27, 2018	Add low band of LoRa	1.2
Mar. 14, 2018	Revise the content of “1 Product Brief”	1.3
Apr. 10, 2018	Update part number	1.4



MtM+ Technology

MtM+ Technology Corporation

7F, 178 MinQuan East Road Section 3,
Songshan District, Taipei,
Taiwan (R.O.C.)

+886-2-7736-7386



<http://www.mtmtech.com.tw>



<http://blog.mtmtech.com.tw>



<https://www.facebook.com/MtMTechologyCorporation>



<http://www.Instagram.com/mtmtech>

© 2018 MtM+ Technology Corporation

DISCLAIMER: The information in this document is provided in connection with MtM+ Technology products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights granted by this document or in connection with the sale of MtM+ Technology products. MTM+ TECHNOLOGY ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL MTM+ TECHNOLOGY BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF MTM+ TECHNOLOGY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. MtM+ Technology makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and products descriptions at any time without notice. MtM+ Technology does not make any commitment to update the information contained herein. MtM+ Technology products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life.

SAFETY-CRITICAL, MILITARY, AND AUTOMOTIVE APPLICATIONS DISCLAIMER: MtM+ Technology products are not designed for and will not be used in connection with any applications where the failure of such products would reasonably be expected to result in significant personal injury or death ("Safety-Critical Applications") without an MtM+ officer's specific written consent. Safety-Critical Applications include, without limitation, life support devices and systems, equipment or systems for the operation of nuclear facilities and weapons systems. MtM+ Technology products are not designed nor intended for use in military or aerospace applications or environments unless specifically designated by MtM+ Technology as military-grade.